

BX35P



SUCTION CUP WITH 21/2 BELLOWS

- ➤ Suitable for level adjustment and for uneven and porous surfaces such as cardboard, etc.
- ▶ In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- ► DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane.
- ► The material DURAFLEX® is mark free.

LIFTING FORCES & TECHNICAL DATA

Material	Material Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm³	mm	mm	g
PU30°/60°	12.0	20.0	28	14.0*	27*	34*	10.0	10.0	14.0	8.0
PU60°	15.0	25	30	22.0*	30*	36*	10.0	10.0	14.0	8.0

^{*}The suction cup is not intended for handling shear lifts. The values are given as a dimensioning guide to be used when, e.g., the acceleration/retardation causes shear forces.

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU30	Yellow transparent	30	10–50
Polyurethane, PU60	Green transparent	60	10–50

MATERIAL RESISTANCE


Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor

^{**}Please contact PIAB.




ORDERING INFORMATION

	Complete suction cups	Art. No.
Α	Suction cup BX35P Polyurethane 30/60 with filter, 1/8" NPSF female	0106604
Α	Suction cup BX35P Polyurethane 30/60 with filter, 1/8" NPSF female, with dual flow control valve	0106605
В	Suction cup BX35P Polyurethane 30/60 with filter, G3/8" male, with mesh filter	0107377
В	Suction cup BX35P Polyurethane 30/60 filter, G3/8" male, mesh filter, dual flow control valve	0107378
	Suction cup BX35P Polyurethane 60 with filter, 1/8" NPSF female	0107561
Α	Suction cup BX35P Polyurethane 60 with filter, 1/8" NPSF female, with dual flow control valve	0107562
В	Suction cup BX35P Polyurethane 60 with filter, G3/8" male, with mesh filter	0107379
В	Suction cup BX35P Polyurethane 60 with filter, G3/8" male, with mesh filter and dual flow control valve	0107380



Rubber parts	Art. No.
Suction cup BX35P Polyurethane 30/60, with filter	0106619
Suction cup BX35P Polyurethane 60, with filter	0107376
Suction cup BX35P, Polyurethane 30/60	0106292
Suction cup BX35P, Polyurethane 60	0107477



Fittings	Art. No.
Fitting 1/8" NPSF female, 30–40	3250005
Fitting 1/8" NPSF female, 30–40, with dual flow control valve	3251006
Fitting G3/8" male, 30–40, with mesh filter	3250086
Fitting G3/8" male, 30–40, with mesh and dual flow control valve	3251009

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.

Spare Part	Material	Temperature range °C	Art. No.
Filter for BX35P	Polyester/TPE	-40–90	0106373