SUCTION CUPS F-MF



F50MF



FLAT SUCTION CUP WITH CLEATS, MARK FREE

- Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- Suitable for flat surfaces.
- ▶ Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.

LIFTING FORCES & TECHNICAL DATA

	force vertical e, N, at vacuu		Lifting force parallel to the surface, N, at vacuum level		Volume	Min. curve radius	Max. vertical movement	Weight rubber part	
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm ³	mm	mm	g
24.5	92	141	31	82	107	10	95	2.0	10

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Thermoelastic polyurethane, TPU	Transparent white	81	-20–80

MATERIAL RESISTANCE


Wear resistance	Oil	Weather & Ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Excellent	Excellent	Excellent	Poor	Poor	Poor	Good	Good

SUCTION CUPS F-MF



ORDERING INFORMATION

Complete suction cups			Art. No.			
A Suction cup F50MF Thermoelas	tic polyurethane, 1/8" NPSF fer	male, with mesh filter	0101791			
A Suction cup F50MF Thermoelas	tic polyurethane, 1/8" NPSF fer	male, with dual flow control valve	0101792			
B Suction cup F50MF Thermoelas	Suction cup F50MF Thermoelastic polyurethane, G1/4" male, with mesh filter					
B Suction cup F50MF Thermoelas	tic polyurethane, G1/4" male, v	with mesh filter and dual flow control	valve 0101793			
C Suction cup F50MF Thermoelas	tic polyurethane, G3/8" male, v	with mesh filter	0101788			
C Suction cup F50MF Thermoelas	tic polyurethane, G3/8" male, v	with mesh filter and dual flow control	valve 0101795			
D Suction cup F50MF Thermoelas	tic polyurethane, 5x1/8" NPSF	female	0101790			
D Suction cup F50MF Thermoelas	tic polyurethane, 5x1/8" NPSF	female, with dual flow control valve	0101797			
2 ⁹ 2			35.5			
<u> </u>	Ø 53 B	¢ 53	Ø 53 D			



Fittings	Art. No
Fitting 1/8" NPSF female, 50, with mesh filter	0101154
Fitting 1/8" NPSF female, 50, with dual flow control valve	3251012
Fitting G1/4" male, 50, with mesh filter	3250092
Fitting G1/4" male, with mesh filter and dual flow control valve	3251013
Fitting G3/8" male, 50, with mesh filter	3250087
Fitting G3/8" male, 50, with mesh filter and dual flow control valve	3251015
Fitting 5x1/8" NPSF female, 50	0100262
Fitting 5x1/8" NPSF female, 50, with dual flow control valve	3251017
Fitting 1/8" NPSF female, 50, PA	3150198

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.