

F75P



FLAT SUCTION CUP WITH CLEATS

- ▶ Suitable for flat and rough surfaces.
- ▶ Fair stability and little inherent movement.
- ► Recommended when the lifting force is parallel to the surface of the object.
- ▶ In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

LIFTING FORCES & TECHNICAL DATA

Material	Lifting force vertical to the surface, N, at vacuum level		Lifting force parallel to the surface, N, at vacuum level			Volume	ıme Min. curve radius	Max. vertical movement	Weight rubber parts	
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm³	mm	mm	g
PU30°/60°	70	193	273	44	176	308	19	150	2	28
PU60°	82	231	330	47	113	169	19	150	2	53

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU30	Yellow	30	10–50
Polyurethane, PU60	Green transparent	60	10–50

MATERIAL RESISTANCE


Wear resistand	Oil e	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellen	t Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


^{**}Please contact PIAB.




ORDERING INFORMATION


	Complete suction cups	Art. No.
Α	Suction cup F75P Polyurethane 30/60, 1/8" NPSF female, with mesh filter	0106349
Α	Suction cup F75P Polyurethane 30/60, G3/8" female, with mesh filter	0106350
Α	Suction cup F75P Polyurethane 30/60, 3/8" NPSF female, with mesh filter	0106351
Α	Suction cup F75P Polyurethane 30/60, G1/2" female, with mesh filter	0106352
Α	Suction cup F75P Polyurethane 60, 1/8" NPSF female, with mesh filter	0111585
Α	Suction cup F75P Polyurethane 60, G3/8" female, with mesh filter	0111586
Α	Suction cup F75P Polyurethane 60, 3/8" NPSF female, with mesh filter	0111587
Α	Suction cup F75P Polyurethane 60, G1/2" female, with mesh filter	0111588
В	Suction cup F75P Polyurethane 30/60, thread insert G3/8" male, with mesh filter	0106830
В	Suction cup F75P Polyurethane 60, thread insert G3/8" male, with mesh filter	0107321
С	Suction cup F75P Polyurethane 30/60, 3/8" NPSF female	0108800
С	Suction cup F75P Polyurethane 60, 3/8" NPSF female	0108801








	Rubber parts	Art. No.
Α	Suction cup F75P Polyurethane 30/60	0104724
Α	Suction cup F75P Polyurethane 60	0111584
В	Suction cup F75P Polyurethane 30/60, for tread insert	0106829
В	Suction cup F75P Polyurethane 60, for tread insert	0107320





Fittings	Art. No.
Fitting 75, G3/8" female, with mesh filter	0100551
Fitting 75, 1/8" NPSF female, with mesh filter	0100548
Fitting 75, G1/2" female, with mesh filter	0100555
Fitting 75, 3/8" NPSF female, with mesh filter	0100553
Thread insert G3/8" male, with 0-ring and mesh filter	0107148

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.